

PATENT APPLICATION

of

Gerald D. Eckstein

David W. Hornbach

Jeffrey A. Moster

for

HYDRAULIC CONTROL APPARATUS FOR A HOSPITAL BED

N1-8029

Attorney Docket 7175-29676

-1-

HYDRAULIC CONTROL APPARATUS FOR A HOSPITAL BEDBackground and Summary of the Invention

5 This invention relates to hydraulic controls for articulating and raising hospital beds and more particularly to a hydraulic control apparatus which uses solenoid valves and an electric pump which can be overridden by manual controls and a manual pump.

10 It is well known for patient support devices such as hospital beds and stretchers to be provided with hydraulic systems which allow the caregiver to raise the height of the bed and articulate a deck underlying the patient support surface to modify the configuration of the patient support surface. When such beds were originally conceived, the control valves and pumps associated with hydraulic cylinders were all manually operated. Manual operation of pumps and control valves can become
15 fatiguing, therefore, articulatable and height adjustable beds were provided with electric motors and electrically controlled valves associated with the hydraulic cylinders. Combinations of electrically controlled pumps and valves and manually operated pumps and valves are also known. One problem with electrically controlled hydraulic cylinders is that during power outages the cylinder cannot be operated and
20 the bed cannot be adjusted. Height adjustment and bed articulation facilitate appropriate treatment of patient injuries, and therefore, loss of the articulation and height adjustment is undesirable in a hospital environment.

Hospital beds with adjustable patient support surfaces moved by hydraulic cylinders which can be controlled either manually or electrically have been
25 provided to address the need for bed adjustment in the event of a power outage. Smith et al., U.S. Patent No. 5,063,624, discloses a manual/electric twin jack bed which provides for manual or electric control of valves and pumps for providing fluids to hydraulic cylinders which will adjust the height of the bed and allow the bed to be configured in Trendelenburg and Reverse Trendelenburg positions.

30 Bailey et al., U.S. Patent No. 4,751,754, discloses a dual hydraulic hospital bed with emergency bypass circuit which provides manually actuated valves and electrically actuated valves for controlling hydraulic cylinders which raise, lower,

and articulate a patient support platform. Both of these dually controlled hydraulic systems appear to use a different set of valves for manual operation and electrical operation of the hydraulic systems. Thus, the hydraulic controls could not easily be retrofitted to a bed previously having only a manual or only an electrically controlled hydraulic system.

Caregivers would appreciate a hydraulic control apparatus for a hospital bed that includes a hilow function and an articulating deck which can be operated manually, electrically, or through a combination of manual and electric operation using a single set of valves. Caregivers and healthcare facilities would appreciate a hydraulic control system allowing manual and electrical operation which could replace the controller on a bed which was operated with only manual controls or only with electrical controls.

According to the present invention a manifold and valve assembly includes a manifold block having an inlet, an outlet, and a conduit in fluid communication with the inlet and with the outlet, a valve having a portion movable within the conduit between a first position blocking fluid communication between the inlet and the outlet and a second position in which the inlet is in fluid communication with the outlet, a solenoid operable to move the valve from the first position to the second position in response to an electrical input applied to the solenoid, and a lever operable to move the valve from the first position to the second position in response to a manual input applied to the lever. The manifold and valve assembly may also include a lock engaging the lever to lock the lever in a position having the valve in the second position. The lock may include a lock solenoid and a lock bar coupled to the lock solenoid, wherein the lock bar engages the lever, and the lock solenoid is operable to move the lock bar in response to an electrical input to the lock solenoid. Often the lever is pivotally coupled to the manifold block and the solenoid is positioned to lie between the manifold block and the lever. The valve may include a stem a part of which is received in an opening in the lever.

According to the present invention a controller for a hospital bed having a bed frame and a support section arranged to receive a portion of a patient's body which is vertically movable with respect to the frame includes a fluid actuated

cylinder attached between the support section and the bed frame, a supply of fluid, a fluid supply path providing fluid communication between the fluid supply and the fluid actuated cylinder, a manually operated pump in the fluid supply path, an electrically operated pump in the fluid supply path, a valve block having a solenoid operated supply valve with manual override in the fluid supply path and designed to selectively interrupt the fluid supply path, an electrical supply actuator connected to the solenoid of the supply valve and to the electrically operated pump to electrically control the interruption of fluid communication between the fluid actuated cylinder and the fluid supply, and a manual actuator connected to the manual override of the supply valve to manually control the interruption of fluid communication between the fluid actuated cylinder and the fluid supply. The controller may also include an electrically actuated manual setting remover coupled to the electrical actuator so that the manual setting is removed upon electrical actuation of the solenoid of the valve. The controller may include a fluid return path providing fluid communication between the fluid supply and the fluid actuated cylinder, a solenoid operated return valve with manual override to selectively interrupt fluid communication between the fluid actuated cylinder and the fluid return path, and an electrical control including the electrical supply actuator and an electrical return actuator connected to the solenoid of the return valve to electrically control the interruption of fluid return path arranged so that the manual supply actuator is also connected to the manual override of the return valve to manually control the interruption of fluid return path.

A valve block in accordance with the present invention includes a fluid supply path, a fluid return path, a valve assembly having a supply member and a return member, a multi-state manual actuator operably connected to the supply member and the return member, an electrical actuator operably connected to the supply member and to the return member, a controller for generating an override signal when the electrically operated actuator is actuated, and a manual actuator override. The supply member of the valve assembly is positionable between a supply interruption position in which the supply member interrupts the fluid supply path and a supply position in which the supply member does not interrupt the fluid supply path while the return member is positionable between a return interruption position in which the return member interrupts the fluid return path and a return position in which the return

member does not interrupt the fluid return path. The multi-state manual actuator is designed and arranged to assume a supply state in which the supply member is in the supply position and the return member is in the return interruption position, a return state in which the return member is in the return position and the supply member is in the supply interruption position, and a neutral state wherein the supply member and the return member are free to assume any position. The electrical actuator selectively positions the supply member between the supply interruption position and the supply position and also selectively positions the return member between the return interruption position and the return position. The manual actuator override is designed and arranged to place the multi-state manual actuator in the neutral state when an override signal is generated.

The valve assembly may include a supply valve and a spaced apart return valve. The supply member may include a supply-opened engagement point and the return member may include a return-opened engagement point and the multi-state manual actuator may include an arm which engages the supply-opened engagement point and does not engage the return-opened engagement point when the multi-state manual actuator is in the supply state, engages the return-opened engagement point and does not engage the supply-opened engagement point when the multi-state manual actuator is in the return state, and does not engage either the supply-opened or return-opened engagement points when in the neutral position. The multi-state manual actuator may include a spring element biasing it in the neutral state, a supply state catch to lock it in the supply state, and a return state catch to lock it in the return state. The override may include a catch engager and a catch engager actuator to position the catch engager between a catch-engaged state in which it engages either the supply catch or the return catch and a catch-disengaged state. The catch engager actuator may include an arm biased to engage either the supply catch or the return catch and a solenoid electromagnetically coupled to the arm to disengage the arm from the supply catch or the return catch when the solenoid is energized. The interrupt signal may cause the solenoid to be energized. The valve assembly may include a supply valve and a spaced apart return valve. The valve block may also include a housing having a mounting surface, and a fulcrum having a first side and a second side mounted to the mounting surface, wherein the arm is pivotally mounted to the fulcrum and the supply

valve is mounted to the mounting surface on the first side of the fulcrum and the return valve is mounted to the mounting surface on the second side of the fulcrum.

A control for a hospital bed having a bed frame, a first support section arranged to receive a first portion of a patient's body and being vertically movable with respect to the frame, and a second support section arranged to support a second portion of a patient's body in accordance with the present invention includes a first fluid actuated cylinder attached between the first support section and the bed frame, a second fluid actuated cylinder attached between the second support section and the bed frame, a supply of fluid, a fluid return path, fluid supply path, a manually operated pump, an electrically operated pump, a valve block including a first valve assembly and a second valve assembly, and a valve controller connected to the first valve assembly and the second valve assembly. The return fluid path provides fluid communication between the fluid supply and the cylinders while the fluid supply path provides fluid communication between the fluid supply and the cylinders. Both the manually operated pump and the electrically operated pump are in fluid communication with the fluid supply path. The first valve assembly is in fluid communication with the first fluid actuated cylinder, the fluid supply path, and the fluid return path. The first valve assembly is designed to selectively interrupt fluid communication between the first fluid actuated cylinder and the fluid supply path and to selectively interrupt fluid communication between the first fluid actuated cylinder and the fluid return path. The second valve assembly is in fluid communication with the second fluid actuated cylinder, the fluid supply path, and the fluid return path. The second valve assembly is designed to selectively interrupt fluid communication between the second fluid actuated cylinder and the fluid supply path and to selectively interrupt fluid communication between the second fluid actuated cylinder and the fluid return path. The valve controller controls the interruption of fluid communication between the first fluid actuated cylinder and the fluid supply path, the first fluid actuated cylinder and the fluid return path, the second fluid actuated cylinder and the fluid supply path, and the second fluid actuated cylinder and the fluid return path. The valve controller is designed to prohibit the first valve assembly from assuming a state in which fluid communication is simultaneously not interrupted between the first fluid actuated cylinder and the fluid return path and the first actuated cylinder and the fluid supply

path and to prohibit the second valve assembly from assuming a state in which fluid communication is simultaneously not interrupted between the second fluid actuated cylinder and the fluid return path and the second actuated cylinder and the fluid supply path.

- 5 Additional objects, features, and advantages of the invention will become apparent to those skilled in the art upon consideration of the following detailed description of the illustrated embodiment exemplifying the best mode of carrying out the invention as presently perceived.

10 Brief Description of the Drawings

Fig. 1 is a perspective view of a hospital bed of the present invention with most of its cover plates removed showing the hydraulic control apparatus extending from the base at the foot of the bed on the right side of the drawing;

- 15 Fig. 2 is a perspective view of the hospital bed of the present invention showing a patient in an elevated position;

Fig. 3 is a view similar to Fig. 2 showing the patient returned to a supine position;

- 20 Fig. 4 is a perspective view of a hospital bed including the hydraulic control apparatus of the present invention with cosmetic moldings and enclosures attached to the bed showing a control panel attached to the foot board, three pedal ends of manual selector levers of a hydraulic controller extending from a cover at the foot of the bed, and a pump bar for actuating a manual pump extending from the same cover;

- 25 Fig. 5 is a schematic circuit diagram for the hydraulic system of the present invention;

- Fig. 6 is a perspective view of a valve housing of the hydraulic controller of the present invention showing solenoid operated valves with manual overrides which are actuated either electrically or manually, and showing manual selector lever arms pivotally mounted to the valve housing with two shafts of the manual overrides extending through slots in each arm;
- 30

Fig. 7 is a side elevation view of the hydraulic controller of Fig. 6 showing a solenoid controlling a lock bar which can lock the lever arms in a depressed

state and which when retracted by solenoid operation will allow the lever arms to return to a neutral position;

Fig. 8 is a sectional view of the hydraulic controller along line 8-8 of Fig. 7;

5 Fig. 9 is a sectional view of the hydraulic controller taken along line 9-9 of Fig. 8 showing the manual overrides of the solenoid operated valves received in slots in the lever arms so that rotation of the lever arm about pivot bar will actuate the manual overrides and showing plungers of the valves in their normally closed position engaging valve seats to interrupt fluid flow between the distribution manifold and a
10 pressure manifold to the left and a return manifold to the right;

Fig. 10 is a sectional view of the hydraulic controller taken along line 10-10 of Fig. 8 showing a mount for a pivot bar to which the lever arms are pivotally mounted and two internal portions of a distribution manifold formed in the valve housing;

15 Fig. 11 is a sectional view taken along line 11-11 of Fig. 8 showing the pressure manifold, release manifold and distribution manifolds of the valve housing;

Fig. 12 is a flow chart of the operation of the hydraulic control apparatus in electrical mode;

Fig. 13 is a view of one of the manual selector lever arms with an
20 angled pedal end, its associated extender valve, its associated retraction valve and the lock bar of the present invention in a neutral position wherein both the extender valve and retraction valve are in their normally closed state and the lock bar abuts a cam formed on an arcuate surface extending from the arcuate surface;

Fig. 14 is a view similar to Fig. 13 showing the lever arm raised to
25 manually open the retraction valve and the lock bar abutting the second end stop in a configuration called the down position;

Fig. 15 is a view similar to Fig. 14 showing the pedal end of the lever arm partially depressed so that the lock bar has ridden to the apex of the cam on the arcuate surface; and

30 Fig. 16 is a view similar to Fig. 15 with the pedal end of the lever arm fully depressed so that the lock bar has ridden over the cam and fallen into an extension notch defined by the cam, arcuate surface, and first end stop locking the

lever arm in an extension position in which the extender solenoid is urged open by manual override and retraction valve is in its normally closed state.

Detailed Description of a Preferred Embodiment of the Invention

5 Fig. 1 illustrates a hospital bed, generally designated by the numeral 10, of the type which is sold by the Hill-Rom Company, Inc. under the designation of Century CC hospital bed modified to include the hydraulic control apparatus 20 of the present invention. Bed 10 illustrated in Fig. 1 is shown with most of the cosmetic moldings and enclosures which normally surround it removed. This is done in order to
10 better see the hydraulic system 30 controlled by the present invention.

Bed 10 includes a base frame 12 which is made up of longitudinal members 14 and 16 which are tied together by a pair of transverse members only one of which, 18, is visible in Fig. 1. Attached to base frame 12 are four large casters designated as 19. Only two of these casters 19 are visible in Fig. 1, but it may be
15 appreciated that the two opposing casters are on the opposite side and serve to support base frame 12 in a mobile fashion.

A valve housing 134 of the hydraulic controller 20 in accordance with the present invention is attached to foot end 11 of base frame 12 of bed 10 as shown, for example, in Figs. 1-4. Hereinafter the term foot end 11 will be applied to various
20 components of bed 10 and of bed 10 itself to designate the end of the component or bed toward which a patient's feet are normally directed. The term head end 13 will be used in a similar fashion. Figs. 2-4 also show a control panel 158 attached to the footboard 84 of bed 10. While in illustrated embodiment hydraulic controller 20 is attached to foot end 11 of bed 10 for operation of the valve housing 134 by the foot of
25 a caregiver, it is to be understood that hydraulic controller 20 may be attached in any convenient location to bed, and may even remain disconnected from bed 10. Valve housing 134 of hydraulic controller 20 also may be configured for operation by the hand or a combination of the hand and foot of the caregiver within the scope of the present invention. Hydraulic controller 20 is only one component of the hydraulic
30 system 30 of bed 10. The remaining lines, valves, cylinders and other components of hydraulic system 30 will be described hereafter.

Returning to Fig. 1, there is shown two generally triangular, vertically extending bosses 22 and 24 attached to the foot end 11 of bed 10. Bosses 22 and 24 serve as a pivot mounting for a cantilevered support arm 26. Cantilevered support arm 26 is hingedly attached to bosses 22 and 24 through a pivot pin 28. Cantilevered arm 26 is attached at its end remote from pivot pin 28 to two brackets 29, only one of which is visible in Fig. 1. Bracket 29 and its corresponding bracket on the opposite side, which is not visible in this view, are attached to two longitudinal frame members 32 and 34. Frame members 32 and 34 are then tied together by transverse members 36 and 38 to form a rigid intermediate frame 37 that will move with brackets 29.

Also attached to bracket 29 is a stabilizing arm 40 which is pivoted to boss 22. Stabilizing arm 40 moves with cantilevered arm 26 to provide a stabilizing function as cantilevered arm 26 moves. Cantilevered arm 26 is driven by a hydraulic cylinder 42 which has an extensible piston or rod 44 that is attached to a clevis mount 46 on cantilever arm 26. Clevis mount 46 has a pin 48 which connects clevis mount 46 to rod 44. The base of cylinder 42 is attached to members 14 and 16.

It may be appreciated that as rod 44 is extended and retracted its movement will in turn be transferred through clevis mount 46 and pin 48 to cantilevered arm 26. Extension and retraction of rod 44 will move cantilevered arm 26 up and down. The position shown in Fig. 1 is an essentially fully extended, or up, position for cantilevered arm 26. It may be appreciated that retraction of rod 44 will then cause cantilevered arm 26 to retract, bringing with it intermediate frame 37 attached to brackets 29. Since cylinder 42 controls the raising and lowering of the support surface of bed 10, commonly called the hilow function, cylinder 42 will be herein after referred to as hilow cylinder 42.

As is the case with many hospital beds, bed 10 includes an articulating deck 39 to achieve various configurations of the patient support surface. Articulating deck 39 is carried by longitudinal frame members 32 and 34. Articulating deck 39 is made up of several elements. There is a fixed seat element 50 which does not move. Adjacent to the head end 13 of bed 10 there is a head portion 52 on which a patient's upper body portion would normally rest and which may be articulated from a fully down position resting on frame numbers 32 and 34 as shown, for example, in Figs. 3 and 4 to the fully up position, as shown, for example, in Figs. 1 and 2. Head portion

52 is raised and lowered through a crank mechanism 54 that is actuated by a hydraulic head cylinder 56 having an extensible piston or rod 58 which is attached to and drives crank mechanism 54. Since cylinder 56 controls the articulation of head portion 52, it will hereinafter be referred to as head cylinder 56.

5 Head cylinder 56 is attached to longitudinal frame member 32 by a bracket 60. In Fig. 1, only one head cylinder 56 is visible to drive head portion 52. However, it is preferred that two head cylinders 56, 56' be used, one carried by frame member 32 and the other on the opposite side carried by frame member 34. Second head cylinder 56' is not visible in Fig. 1, but it is shown schematically in Fig. 5. The
10 head elevation function would work with only one head cylinder 56, but two cylinders 56, 56' provide a smoother motion and less chance of binding of crank mechanism 54.

Two additional portions of articulating deck 39 are a thigh portion 62 and a leg portion 64. Thigh portion 62 and leg portion 64 are pinned together so that they move as a unit. Thigh portion 62 and leg portion 64 are also pinned to fixed seat
15 portion 50 so that they may be elevated as shown in Fig. 1. Actuation of thigh portion 62 will cause corresponding raising of leg portion 64. Thigh portion 62 is raised and lowered by a hydraulic cylinder 66 having an extensible piston or rod 68 that is attached to thigh portion 62. Since cylinder 66 controls the articulation of leg portion 64, it will hereinafter be referred to as leg cylinder 66. Extension and retraction of rod
20 68 will cause corresponding movement of thigh portion 62 and leg portion 64.

None of the hydraulic piping or valves necessary for operation of this system 30 are shown in Fig. 1 to avoid unnecessary complication. Fig. 1 does show in phantom lines that a reservoir 70 for hydraulic fluid is carried between vertical bosses 22 and 24. Also carried between bosses 22 and 24 is a power pack 72 including an
25 electric motor 76 and a pump 78 (see Fig. 5) for providing electrical pumping power for hydraulic system 30 and a manual pump 102.

As shown, for example, in Figs. 5 and 11, hydraulic controller 20 includes a valve housing 134 having a pressure manifold 136, a return manifold 138, a distribution manifold 140, a pressure inlet 142, a return outlet 144, a hilow port 146, a
30 head port 148, and a leg port 150. Hydraulic controller 20 also includes three solenoid controlled extension valves with manual overrides 92, 94, 96 extending through valve housing 134 to interrupt fluid flow between pressure manifold 136 and distribution

manifold 140 and three solenoid controlled retraction valves with manual overrides 110, 128, and 118 extending through valve housing 134 to interrupt fluid flow between return manifold 138 and distribution manifold 140. Thus extension valve 92 and retraction valve 110 are associated with hilow cylinder 42, extension valve 96 and
5 retraction valve 128 are associated with head cylinders 56, 56', and extension valve 94 and retraction valve 118 are associated with leg cylinder 66.

Each solenoid operated valve with manual override 92, 94, 96, 110, 118, 128 includes an inlet 178, an outlet 180 in fluid communication with inlet 178, a valve seat 182 disposed in the fluid communication path between the inlet 178 and
10 outlet 180, a solenoid 184, and a magnetic shaft 186 as shown, for example, in Fig. 9. Magnetic shaft 186 extends through, and is mounted for movement with respect to, solenoid 184 and is responsive to energization of solenoid 184. Each magnetic shaft 186 includes a manual override portion 188 extending externally from solenoid 184 and a plunger end 190 designed to engage valve seat 182 to interrupt fluid
15 communication between inlet 178 and outlet 180. Shaft 186 is biased by a spring 192 (See Fig. 5) in the normally closed position in which plunger end 190 engages valve seat 182 and interrupts the fluid communication between inlet 178 and outlet 180. Manual override portion 188 of shaft 186 includes an upper end 198 having a diameter 200, and a slender shaft 202 extending between plunger end 190 and upper end 198
20 and having a diameter 204 less than diameter 200 of upper end 198, as shown, for example, in Fig. 9.

Valve housing 134 of hydraulic controller 20 also includes a pivot bar 206 attached to and displaced from valve housing 134, three lever arms 208, 210, 212 pivotally mounted to pivot bar 206, two override solenoids 214 mounted to opposite
25 ends of valve housing 134, and a u-shaped lock bar 216. Lock bar 216 includes two magnetic portions 218 extending through, and moveable with respect to, solenoid 214 between an extended position and a retracted position in response to solenoid 214 energization. Lock bar 216 is biased in the extended position by springs 220. Each lever arm 208, 210, 212 is substantially identical and includes an extension control
30 section 222 extending between pivot point 224 and extension end 226, a retraction control section 228 extending between pivot point 224 and pedal end 230 having a portion substantially parallel to extension control section 222, a pedal 231 attached to

pedal end 230, and a lock bar-engaging section 232 extending substantially perpendicular to extension and retraction control sections 222, 228. Lock bar-engaging section includes an arcuate lock bar-engaging surface 234 displaced from and focused about pivot point 224. Extending radially from arcuate surface 234 are first end stop 236, second end stop 238, and extension lock cam 240. Extension lock cam 240 is displaced from center 242 of arcuate surface 234 toward first end stop 236 by a distance 244 substantially equal to radius 246 of lock bar 216, as shown, for example, in Fig. 9.

Lever arm 210, as well as lever arms 208, 212, includes a longitudinally extending extension shaft-receiving slot 248 formed in extension control section 222 and a longitudinally extending retraction shaft-receiving slot 250 formed in retraction control section 228. Each shaft-receiving slot 248, 250 has a width greater than diameter 204 of slender shaft 202 but less than diameter 200 of upper end 198. Each lever arm 208, 210, 212 is biased by spring 254 extending between valve housing 134 and extension control section 222 and spring 256 extending between valve housing 134 and retraction control section 228 to be urged into a neutral position in which extension control section 222 and retraction control section 228 are substantially parallel to top of valve housing 134.

Each lever arm 208, 210, 212 is associated with a particular cylinder 42, 66, 56 and controls the extension and retraction valves associated with that particular cylinder. Lever arm 208 is associated with hilow cylinder 42 so slender shaft 202 of extension valve 92 is received in extension shaft-receiving slot 248 and slender shaft 202 of retraction valve 110 is received in retraction shaft-receiving slot 250 of lever arm 208. Lever arm 210 is associated with head cylinders 56, 56' so slender shaft 202 of extension valve 96 is received in extension shaft-receiving slot 248 and slender shaft 202 of retraction valve 128 is received in retraction shaft-receiving slot 250 of lever arm 210. Lever arm 212 is associated with leg cylinder 66 so slender shaft 202 of extension valve 94 is received in extension shaft-receiving slot 248 and slender shaft 202 of retraction valve 118 is received in retraction shaft-receiving slot 250 of lever arm 212.

When any lever arm 208, 210, 212 is in neutral position, as shown, for example, in Figs. 6-10 and 13, normally closed extension valves 92, 96, 94 and

retraction valves 110, 128, 118 associated with lever arms 208, 210, 212 return to, or remain in, their normally closed positions. Upper end 198 of manual override portion 188 of shaft 186 of extension valve 92, 96, 94 is slightly above top surface 258 of lever arm 208, 210, 212 adjacent to extension shaft-receiving slot 248. Likewise, upper end

5 198 of manual override portion 188 of shaft 186 of retraction valve 110, 128, 118 is slightly above top surface 258 of lever arm 208, 210, 212 adjacent to retraction shaft-receiving slot 250. Thus when a lever arm 208, 210, 212 is in neutral position each of its associated valves is closed. Also, lock bar 216 engages center 242 of arcuate surface 234 and abuts cam 240, as shown, for example, in Figs. 6, 7, 10, 12. The

10 portion of arcuate surface 234 immediately adjacent to cam 240 on the side closer to second end stop 238 to both sides of center 242 is the neutral surface 243.

When a pedal 231 of a lever arm 208, 210, 212 is depressed, lever arm 208, 210, 212 pivots about pivot bar 206, lock bar 216 rides over cam 240 compressing springs 220 while passing over cam 240 as shown, for example, in Fig.

15 15, until lock bar 216 reaches extension portion 260, i.e. between cam 240 and first end stop 236, of arcuate surface 234 allowing springs 220 to again expand as shown, for example, in Fig. 16. Top surface 258 of lever arm 208, 210, 212 adjacent extension shaft-engaging slot 248 pivots upwardly to engage upper end 198 of manual override portion 188 of shaft 186 of extension solenoid 92, 96, 94 to urge shaft 186

20 upward causing plunger 190 to disengage valve seat 182. Retraction control section 228 pivots downwardly allowing retraction valves 110, 128, 118 to remain in their normally closed states. Springs 220 have greater spring constants than springs 254, 256 so springs 254, 256 cannot force lock bar 216 to again ride over cam 240 and return to neutral position 243, i.e. near center 242 of arcuate surface 234, so lever arm

25 208, 210, 212 is locked in its depressed state even if caregiver removes pressure from the pedal 231. While lock bar 216 rides over cam 240 of a lever arm 208, 210, 212 which is having its pedal 231 depressed, any previously depressed lever arm 208, 210, 212 which is not also being depressed will return to the neutral position because springs 254, 256 will urge cam 240 to ride over the depressed lock bar 216.

30 When a pedal 231 of a lever arm 208, 210, 212 is lifted, extension control section 222 pivots downwardly allowing extension valve 92, 96, 94 to return to, or remain in, its normally closed position, retraction control section 228 pivots

upwardly causing top surface 258 of lever arm 208, 210, 212 adjacent to retraction shaft-receiving slot 250 to engage upper end 198 of manual override portion 188 of shaft 186 inducing plunger 190 to disengage from valve seat 182 opening retraction valve 110, 128, 118 as shown, for example, in Fig. 14. Since there is no cam between neutral portion 243 of arcuate surface 234 and second end stop 238, lock bar 216 remains in its extended position and rides along arcuate surface 234 between neutral portion 243 and retraction portion 262. When caregiver ceases lifting pedal 231, springs 254, 256 return lever arm 208, 210, 212 to the neutral position. While the invention is described as having two springs 254, 256 urging each lever arm 208, 210, 212 to the neutral position, this same biasing function could be performed by a single spring extending between housing and lever arm, a torsion bar, or some other position restoring mechanism within the teachings of this invention.

As shown, for example, in Figs. 1, 2, 3, and 4, lever arms 208, 210, 212 and a pump bar 74 for operation of the hydraulic system 30 of the present invention in a manual mode extend from a cover 71. Pump bar 74 is an actuator for manual pump 102. By pumping on pump bar 74 a caregiver will provide hydraulic pressure to the system 30 generated by manual pump 102. The hydraulic pressure thus provided may be directed by operation of lever arms 208, 210, 212 connected to the slender shaft 202 of manual override portion 188 of magnetic shaft 186 of solenoid operated valves 92, 94, and 96 to the appropriate cylinder 42, 56, 66 as previously stated. Lever arms 208, 210, 212 are used in a manual operation mode as will be shown with respect to the discussion of the hydraulic circuit 30 of the present invention.

Manual overrides of solenoid operated valves 92, 96, and 94 are operated by lever arms 208, 210, 212 which may be actuated by depressing pedal 231 attached to pedal end 230 of lever arms 208, 210, 212 pivotally mounted to valve housing 134 as previously described. Likewise manual overrides 188 of solenoid operated valves 110, 118, 128 are also actuated by lever arms 208, 210, 212. Override portion 188 of shaft 186 of valve 92 which controls extension of hi-low cylinder 42 is attached on the opposite side of pivot point 224 of lever arm 208 from override portion 188 of shaft 186 of valve 110 which controls retraction of hi-low cylinder 42 as shown, for example, in Figs 6, 7. Override portion 188 of shaft 186 of valve 94 which controls extension of leg cylinder 66 is attached on the opposite side of pivot point 224

of lever arm 212 from override portion 188 of shaft 186 of valve 118 which controls retraction of leg cylinder 66 as shown, for example, in Figs. 6, 7. Override portion 188 of shaft 186 of valve 96 which controls extension of head cylinders 56, 56' is attached on the opposite side of pivot point 224 of lever arm 210 from override portion 188 of shaft 186 of valve 128 which controls retraction of head cylinder 56, 56' as shown, for example, in Figs. 6, 10.

To manually raise a component of bed 10, a caregiver depresses pedal 231 of lever arm 208, 210, 212 associated with the desired component until it locks in its depressed position which opens extension valve 92, 96, 94 associated with the component and closes retraction valve 110, 128, 118 associated with the component, respectively. The caregiver then repeatedly depresses pump bar 74 allowing pump bar 74 to return to its normal location between depressions to operate manual pump 102. When the desired component reaches the desired level of extension, caregiver ceases depressing pump bar 74. Caregiver may then unlock the lever arm 208, 210, 212 by lifting and releasing pedal 231, or may leave lever arm 208, 210, 212 in its locked state.

To manually lower a component by releasing pressure provided to the system 30, the component's associated lever arm 208, 210, 212 is lifted allowing its associated extension valve 92, 96, and 94 to close or remained closed while forcing its associated retraction valve 110, 128, and 118 open allowing hydraulic pressure to be released from hydraulic system 30 so that the components of bed 10 may be lowered. Releasing lever arm 208, 210, 212 prior to full retraction of the desired component will cause its associated retraction valve 110, 128, 118 to return to its normally closed state causing the desired component to be maintained at its degree of extension at the time of release of lever arm 208, 210, 212. Lever arms 208, 210, 212 control lowering of the hilow function, the head portion, and the foot portion, respectively, by holding open valves 110, 128, 118 respectively only while lever arms 208, 210, 212 are held in the raised position. If lever arms 208, 210, 212 are released, they will spring to a neutral position allowing normally closed valves 110, 128, and 118 respectively to close.

Referring to Fig. 2, bed 10 is shown with a patient 80 occupying the sleep surface which has been raised to the position generally shown in Fig. 1. A

headboard 82 and a footboard 84 have been added to bed 10 as would normally be the case in use. Attached to footboard 84 is a control panel 158 used to operate the hydraulic control apparatus in electrical mode. Fig. 3 shows patient 80 having reached the fully flat position from the position shown in Fig. 2.

5 Fig. 5 shows the hydraulic circuit 30 of the present invention in a standard hydraulic schematic form. Power pack 72 is seen to consist of an electric motor 76 driving a pump 78 which when actuated provides hydraulic fluid through line 89 to line 90. Alternatively, manual pump 102 when actuated provides pressurized hydraulic fluid through line 100 to line 90. Line 90 is connected to pressure inlet 142
10 of valve housing to be in fluid communication with pressure manifold 136 which splits to feed the inlets 178 of the three extension valves 92, 94 and 96. Each of these valves 92, 94, 96 serve as extension valves which when open allow pressurized hydraulic fluid to flow into hilow cylinder 42, leg cylinder 66, and head cylinders 56, 56' respectively. Each of these valves 92, 94, 96 are normally closed and only allow fluid flow when
15 their solenoid 184 is energized or when valve is actuated by manual override portion 188.

Solenoid valve 92, when open, will allow pressurized hydraulic fluid from pressure manifold 136 to flow through the hilow branch 139 of distribution manifold 140, hilow port 146, and line 147 to hilow cylinder 42 which raises bed 10.
20 Hilow branch 139 of distribution manifold 140 includes pressure branch 98 and return branch 112. The pressurized hydraulic fluid in pressure manifold 136 is supplied from line 90 through pressure inlet 142. The pressurized hydraulic fluid in line 90 may be provided through line 89 extending from electric pump 78 or line 100 extending from manual pump 102. Thus, hilow cylinder 42 is able to receive hydraulic fluid
25 pressurized by either electric pump 78 or manual pump 102 through valve 92.

Line 89 extending from electric pump 78 and line 100 extending from manual pump 102 merge to form line 90 as shown schematically, for example, in Fig. 5. Line 89 is formed to include a check valve 88. Line 100 is also formed to include a check valve 108. When electric pump is operated the pressurized hydraulic fluid opens
30 check valve 88 and closes check valve 108 to prevent back flow through manual pump 102. When manual pump 102 is operated check valve 108 is opened and check valve 88 is forced shut to prevent back flow through electric pump 78. If one of extension

valves 92, 94, 96 remains open after either pump 78, 102 ceases operation (as often occurs during manual operation), check valves 108 and 88 are closed by back pressure of hydraulic fluid in line 90.

Both foot pump 102 and power pack 72 draw hydraulic fluid from
5 hydraulic reservoir 70. Reservoir 70 serves as a source for the hydraulic fluid to the entire system 30. Before the hydraulic fluid enters power pack 72 or foot pump 102, it passes from reservoir 70 through line 103, filter 104, and line 105. There is a separate branch line 106 which connects line 105 to foot pump 102.

Returning now to hydraulic hilow cylinder 42, hilow cylinder 42 is of
10 the single acting type. That is its rod 44 is extended by supplying pressurized hydraulic fluid through line 147 to hilow cylinder 42. If solenoid valve 92 is then closed, pressure will be trapped in line 147 and pressure branch 98 of hilow branch 139 of distribution manifold 140 and rod 44 will remain extended. To retract rod 44, solenoid valve 110 is actuated to allow fluid to flow back along line 147 through hilow port 146
15 then through release branch 112 of hilow branch 139 of distribution manifold 140 into solenoid valve 110, from whence the fluid exits through return manifold 138, return outlet 144, and return line 114 to return to reservoir 70. With pressure trapped in line 147, pressure branch 98 and release branch 112 of hilow branch 139 of distribution manifold 140, and solenoid valves 92 and 110 both closed, rod 44 will stay in the
20 position where it was placed. If valve 92 has been manually actuated by lever arm 208, it will typically remain open until closed as previously described. In the case of manual actuation of valve 92, check valves 88, 108 prevent fluid from returning to reservoir 70 through either electric pump 78 or manual pump 102.

When solenoid valve 110 is actuated, either manually or electrically, rod
25 44 will slowly retract as a result of the weight on it, and thus bring cantilevered arm 26 downward and retract entire bed 10 toward the floor. When rod 44 has reached the desired extended position releasing lever arm 208 or de-energizing solenoid 184 causes valve 110 to close leaving line 147 pressurized. In order to relieve the pressure, lever arm 208 may be raised, or solenoid 184 energized, to actuate valve 110 and allow
30 hydraulic fluid to return to reservoir 70.

The operation of all of cylinders 42, 56, and 66 are substantially identical to the operation thus described. Solenoid valves 92, 94 and 96 are all

identical and may be electrically operated from control panel 158 located on the bed 10, either in the siderail or at the foot 11 of bed 10, as shown, for example in Fig. 4. Pump outlet line 90 provides pressurized hydraulic fluid to pressure manifold 136 which is also connected to inlet 178 of the normally closed solenoid valve 94. Pressure
5 portion 116 of leg portion 141 of distribution manifold 140 is in fluid communication with outlet 180 of normally closed solenoid valve 94. Leg portion 141 is connected through leg port 150 and line 151 to leg cylinder 66 which operates thigh and leg
10 portions 62, 64 of articulating deck 39. In the electrically operated mode, pressure from pump 78 will flow through line 89, line 90, pressure inlet 142, pressure manifold 136, and, if solenoid valve 94 is actuated to its open position, then through pressure
branch 116 of leg branch 141 of distribution manifold 140, leg port 150, and line 151 operate leg cylinder 66 and extend rod 68. This then will move thigh portion 62 and
leg portion 64 to the upright position shown in Fig. 1. When solenoid valve 94 is
15 closed, pressure will remain in line 151 and rod 68 will remain in the position where it was placed.

In order to retract rod 68 and allow thigh portion 62 and leg portion 64 to return to their flat position, a normally closed solenoid valve 118 is opened. Inlet 178 of solenoid valve 118 is connected to a release branch 120 of leg branch 141 of
20 distribution manifold 140 which is in fluid communication through leg port 150 with line 151 coupled to leg cylinders 66. Outlet 180 of solenoid valve 118 is then connected to reservoir 70 through release manifold 188, return outlet 144, and return
line 114. Thus, actuation of the solenoid valve 118 by energizing its solenoid 184 will allow the pressurized hydraulic fluid extending leg cylinder 66 to be released by
returning the hydraulic fluid to reservoir 70 through line 151, leg port, 150, leg portion
25 141 of distribution manifold 140, return manifold 138, return outlet 144, and return line 114. This will allow rod 68 to retract.

During manual mode of operation of leg cylinder 66, lever arm 212 and manual pump 102 are operated in a manner similar to that previously described with
30 respect to the hilow cylinder 42. Lever arm 212 is depressed causing manual overrides 188 to close valve 118 and open valve 94. Operation of foot powered pump 102 by pump bar 74 generates pressurized hydraulic fluid which will flow from reservoir 70 through pump lines 103, 105, and 106 to 102, then through line 89 and 90, pressure

inlet 142, pressure manifold 136, valve 94, pressure branch 116 of leg branch 141 of distribution manifold 140, leg port 150, and line 151 to extend rod 68 of leg cylinder 66. Ceasing operation of foot pump 102 will cause the pressurized fluid to remain in cylinder 66 and lines 151 maintaining rod 68 in the position which it was in at the time operation was ceased. Raising pedal 231 of lever arm 212 will cause manual overrides 188 to close valve 94 and open valve 118. Pressurized fluid will then return from cylinder 66 through line 151, leg port 150, return branch 120 of leg branch 141 of manifold 140, valve 118, return manifold 138, return outlet 144, and line 114 to reservoir 70 allowing rod 68 to retract. If lever arm 212 is released at any time during retraction of arm 68, valve 118 will close and arm 68 will remain extended to the extent that it was extended at release of lever arm 212.

Fig. 1 showed only one head cylinder 56 operating head portion 52, the actual configuration of two cylinders is shown in Fig. 5. These cylinders are designated as 56 and 56'. Head cylinders 56 and 56' are both operated simultaneously through solenoid valves 96 and 128. Inlet 178 of solenoid valve 96 is connected through pressure manifold 136, pressure inlet 142, line 90, and line 89 to power pack 72. Solenoid valve 96 is a normally closed valve and its actuation will allow pressurized operating fluid to simultaneously flow to both head cylinders 56 and 56' through pressure branch 124 of head branch 143 of manifold 140, head port 148, line 149 and branch connectors 125 and 126. Actuation of head cylinders 56 and 56' will cause their respective rods 58 and 58' to be extended and raise the head portion 52 as seen in Fig. 1. Pressurized hydraulic fluid is trapped in lines 149, 125 and 126 by closing solenoid valve 96 after the pressurized fluid has been furnished and rods 58 and 58' have been extended.

To release the pressure on head cylinders 56 and 56', solenoid valve 128 which is normally closed is opened. This then allows the operating fluid in head cylinders 56 and 56' to flow through branch lines 125, 126, line 149, leg port 118, and return branch 130 of head branch 143 of distribution manifold 140 to solenoid valve 128. When solenoid valve 128 is opened, the operating fluid will then flow through return manifold 138, return port 144, and line 114 to reservoir 70.

Solenoid valves with manual overrides 94, 96, 118, 128, all serve as a first hydraulic control valve means to control functioning of head portion 52, thigh

portion 62, leg portion 64 and their associated operating hydraulic cylinders. Solenoid valves with manual overrides 98 and 110 serve as a second hydraulic control valve means to control the hilow function of bed 10 and hilow cylinder 42.

Solenoid valves 118 and 128 are fixed to allow a certain flow of
5 hydraulic fluid through them when they are actuated. This flow is calculated to allow a relatively gradual lowering of the portions which they control. This avoids unnecessary jarring and uncomfortable feelings on the part of the patient.

Fig. 4 shows footboard 84 of the type usually used with the bed 10. Footboard 84 is attached to foot end 11 of bed 10. A bed control panel 158 is hooked to footboard 84. While illustrated control panel 158 is shown hooked to footboard 84,
10 it is to be understood that it may be incorporated into a housing in footboard 84, attached to or incorporated into headboard 82 or a side rail, or remain unattached to bed 10. Control panel 158 carries a number of electrical switches which control various functions. The illustrated control panel 158 includes a head up switch 160, a
15 head down switch 162, a leg up switch 164, a leg down switch 166, a hilow up switch 168, and a hilow down switch 170.

Each switch is normally open and is electrically connected to not only the valve housing 134 but also to the solenoids 214 controlling the lock bar 216. Upon actuation of any of the switches 160, 162, 164, 166, 168, 170, a circuit is closed
20 to energize solenoids 214 inducing retraction of lock bar 216. With lock bar 216, retracted lever arms 208, 210, 212 return to the neutral position allowing the normally closed valves 92, 96, 94, 110, 128, 118 to close or remain closed. This removes any valve settings which may had been manually entered previously through actuation of lever arms 208, 210, 212. Head up switch 160 turns on power pack 72 and opens
25 valve 96 by energizing its solenoid 184. This causes head portion 52 to be raised by the action of cylinders 56 and 56'. Head down switch 162 is electrically connected to solenoid 184 of head retraction valve 128 and lock bar solenoids 214. Actuation of head down switch 162 will open valve 128 by energizing its solenoid 184 allowing hydraulic fluid to return to reservoir 70 and head portion 52 to drop.

30 Leg up switch 164 will turn on power pack 72 and open valve 94 by energizing its solenoid 184. This will cause leg cylinder 66 to operate and raise thigh portion 62 and leg portion 64. Conversely operation of a leg down switch 166 will

open valve 118 by energizing its solenoid 184, causing hydraulic fluid to return to reservoir 70 and thigh portion 62 and leg portion 64 to return to their horizontal position.

When hilow up switch 168 is operated, power pack 72 will operate and valve 92 will be opened by its energized solenoid 184. This will cause hilow cylinder 42 to operate and raise bed 10. To lower bed 10, a hilow down switch 170 is activated. This will cause valve 110 to open in response to its energized solenoid 184 and allow hydraulic fluid to return to reservoir 70 through valve 110.

Operation of any of the switches 160, 162, 164, 166, 168, or 170 will initially actuate solenoids 24 which will retract lock bar 216 causing all spring loaded lever arms 208, 210, 212 to return to their neutral positions allowing all valves 92, 94, 96, 110, 118, and 128 to return to their normally closed positions unless the solenoid 184 of that particular valve is currently being energized.

While hydraulic control apparatus 20 has been described as having three lever arms 208, 210, 212 each associated with a two port two position (2 X 2) extension valve 92, 96, 94 and a 2 X 2 port two position retraction valve 110, 128, 118, it is within the teaching of the invention to have a single three port three position (3 X 3) normally closed solenoid actuated valve with manual override attached to each lever arm for controlling the extension and retraction of its associated component. It is also within the teaching of the invention to have less than three or more than three hydraulic components controlled by the apparatus by adding or subtracting the appropriate number of extension valves, retraction valves, lever arms, up buttons and down buttons.

The hydraulic control apparatus 20 need not be an original component supplied with a bed but may be used to upgrade beds with hydraulic systems 30 which do not currently provide both manual and electrical control of the hydraulic system 30.

It is also envisioned that in the event of power pack 72 failure, pump bar 74 could be manipulated while one of the up switches 160, 164, 168 is actuated to supply pressurized hydraulic fluid with manual pump 102 through an electrically actuated extension valve 96, 94, 92 to a hydraulic cylinder 56, 66, 42. In the unlikely event of failure of solenoids 184 of extension valves 96, 94, 92, lever arms 212, 210, 208 could be depressed while up switches 160, 164, 168 are actuated so that

pressurized hydraulic fluid generated by electric pump 76 can be supplied to a hydraulic cylinder 56, 66, 42 through a manually actuated valve 96, 94, 92.

- Although the invention has been described in detail with reference to a certain illustrated embodiment, variations and modifications exist within the scope and
- 5 spirit of the invention as described and defined in the following claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211